

optical axis is in particular parallel to the direction of light emission 15 of the light emitting elements (e.g., laser diodes).

Page 13, lines 20-25, please delete the paragraph in its entirety and substitute therefor:

b2 When the subassembly 10 is fixed on the bracket 7, at first the engaging section 2a of the holder 2 is inserted in an engaging hole 7a formed on substantially the center of the bracket 7 such that the engaging section 2a can rotate in a direction indicated by an arrow E.

Then the subassembly 10 is fixed to the bracket 7 by screwing screws 9 to holes 2d.

#### IN THE CLAIMS

Please cancel Claims 2, 7, 12, and 17 without prejudice or disclaimer.

Please amend Claims 1, 3, 6, 8, 11, 13, 16, 18, and 21 as shown in clean form below:

Sub 7  
C1 b3

1. (Twice Amended) A multi-beam scanning device comprising:  
a laser diode array having at least three light emitting points arranged in a package at an equal interval and configured to emit respective laser beams that form corresponding laser beam spots on a recording medium at a minimum recording interval, wherein  
the laser beams from the at least three light emitting points scan the recording medium in a main scanning direction while being at least one of on and off so as to form a light image having the minimum recording interval in the recording medium,  
the equal interval is not greater than the minimum recording interval,  
the at least three light emitting points are arranged such that the corresponding laser beams spots on the recording medium are arranged substantially in a line in a direction orthogonal to the main scanning direction, and  
wherein any one of the laser beams is used as a clock laser beam configured to determine a timing of starting each main scanning.

Sub  
C.1  
cont  
b4

3. (Amended) The multi-beam scanning device according to Claim 1, further comprising:

an abnormal lighting detector configured to detect abnormal lighting of the one of the at least three light emitting points configured to emit the clock laser beam; and

a laser beam changer configured to change the clock laser beam to any one of the laser beams emitted by the other light emitting points normally emitting a laser beam, when the abnormal lighting detector detects abnormal lighting.

b5

6. (Twice Amended) An image forming apparatus comprising:

a recording medium; and

a laser diode array having at least three light emitting points arranged in a package at an equal interval and configured to emit respective laser beams that form corresponding laser beam spots on the recording medium at a minimum recording interval, wherein

the laser beams from the at least three light emitting points scan the recording medium in a main scanning direction while being at least one of on and off so as to form a light image having the minimum recording interval on the recording medium,

the equal interval is not greater than the minimum recording interval,

the at least three light emitting points are arranged such that the corresponding laser beam spots on the recording medium are arranged substantially in a line in a direction orthogonal to the main scanning direction, and

wherein any one of the three or more laser beams is used as a clock laser beam configured to determine a timing of starting each main scanning.

b6

8. (Amended) The image forming apparatus according to Claim 6, further comprising:

an abnormal lighting detector configured to detect abnormal lighting of one of the at least three light emitting points configured to emit the clock laser beam; and

Sub  
Cont

a laser beam changer configured to change the clock laser beam to any one of the laser beams emitted by the other light emitting points normally emitting a laser beam, when the abnormal lighting detector detects abnormal lighting.

11. (Twice Amended) A multi-beam scanning device comprising:  
a laser emitting means for emitting laser beams, comprising at least three light emitting points arranged in a package at an equal interval and configured to emit the at least three laser beams to form corresponding laser beam spots on a recording medium at a minimum recording interval,

wherein the laser beams from the at least three light emitting points scan the recording medium in a main scanning direction while being at least one of on and off so as to form a light image having the minimum recording interval on the recording medium,

the equal interval is not greater than the minimum recording interval,

the at least three light emitting points are arranged such that the corresponding laser beam spots on the recording medium are arranged substantially in a line in a direction orthogonal to the main scanning direction, and

any one of the laser beams is used as a clock laser beam configured to determine a timing of starting each main scanning.

13. (Amended) The multi-beam scanning device according to Claim 11, further comprising:

an abnormal lighting detection means for detecting abnormal lighting of one of the at least three light emitting points configured to emit the clock laser beam; and

a laser beam changing means for changing the clock laser beam to any one of the laser beams emitted by the other three light emitting points normally emitting a laser beam, when the abnormal lighting detection means detects abnormal lighting.

16. (Twice Amended) An image forming apparatus comprising:

Sub  
Cmt

means for recording data thereon; and  
means for emitting laser beams, comprising at least three light emitting points arranged in a package at an equal interval and for emitting laser beams to form corresponding laser beam spots on the means for recording at a minimum recording interval,  
wherein the laser beams scan the means for recording in a main scanning direction while being at least one of on and off so as to form a light image having the minimum recording interval on the means for recording,  
the equal interval is not greater than the minimum recording interval,  
the at least three light emitting points are arranged such that the corresponding laser beam spots on the means for recording are arranged substantially in a line in a direction orthogonal to the main scanning direction, and  
any one of the laser beams from the at least three light emitting points is used as a clock laser beam for determining a time to start each main scanning.

~~610~~ 18. (Amended) The image forming apparatus according to Claim 16, further comprising:

means for detecting abnormal lighting of the at least three light emitting points that is used to emit the clock laser beam; and

means for changing the clock laser beam to any one of the laser beams emitted by the other three light emitting points, when the means for detecting abnormal lighting detects an abnormal lighting condition.

~~611~~ 21. (Twice Amended) A multi-beam scanning device comprising:

a light beam emitting array comprising three or more light emitting elements, which are arranged at predetermined locations and which emit respective laser beams to form corresponding laser beam spots on a recording medium at a minimum recording interval,

Sub  
Cont

wherein the three or more laser beams scan the recording medium in a main scanning direction while being put on or off to form a light image having the minimum recording interval on the recording medium,

wherein the three or more light emitting elements are arranged such that the corresponding laser beam spots on the recording medium are arranged substantially in a line in a direction orthogonal to the main scanning direction, and

any one of the laser beams from the at least three light emitting points is used as a clock laser beam for determining a time to start each main scanning.

---

Please add new Claims 27-31 as shown below:

---

~~b2~~ 27. (New) A multi-beam scanning device, comprising:

a laser diode array having at least three light emitting points arranged at an equal interval and configured to emit respective laser beams that form corresponding laser beam spots on a recording medium at a minimum recording interval,

wherein the at least three laser beams from the at least three light emitting points scan the recording medium in a main scanning direction to form a light image having the minimum recording interval in the recording medium,

the equal interval is not greater than the minimum recording interval, and

one of the at least three laser beams is configured to be used as a clock laser beam to determine a starting time for each scanning.

28. (New) An image forming apparatus comprising:

a recording medium; and

Sub  
Cont

a laser diode array having at least three light emitting points arranged at an equal interval and configured to emit respective laser beams that form corresponding laser beam spots on the recording medium at a minimum recording interval,

wherein the at least three laser beams from the at least three light emitting points scan the recording medium in a main scanning direction to form a light image having the minimum recording interval on the recording medium,

the equal interval is not greater than the minimum recording interval, and

one of the at least three laser beams is configured to be used as a clock laser beam to determine a starting time for each scanning.

29. (New) A multi-beam scanning device comprising:

a laser emitting means for emitting laser beams, comprising at least three light emitting points arranged at an equal interval and configured to emit the at least three laser beams to form corresponding laser beam spots on a recording medium at a minimum recording interval,

wherein the at least three laser beams from the at least three light emitting points scan the recording medium in a main scanning direction to form a light image having the minimum recording interval on the recording medium,

the equal interval is not greater than the minimum recording interval, and

one of the at least three laser beams is configured to be used as a clock laser beam to determine a starting time for each scanning.

30. (New) An image forming apparatus comprising:

means for recording data thereon; and

Cont  
b12